

## Falco Thinner 1050

### Product Description

A Quick air-drying Virgin Grade Thinner with high solvency and low odour thinner for multipurpose usage for routine cleaning and paint mixing.

### Main Characteristic

The **Falco Thinner 1050** is commonly used for mixing Enamel paints as well as cleaning dried droplets of paint on floors and metals, Cleaning of Spray Gun and Painting Equipment, Mixing with Primers, Lacquers and Sealers. compatible with Enamel paints

### Technical Data

<b>Colour</b>	: Transparent Clear
<b>Specific Gravity</b>	: 0.835 +/- 2%
<b>Flash Point</b>	: < 21°C
<b>Evaporation</b>	: 2.22 +/- 5% ..... Butac = 1
<b>Application</b>	: Brush, Conventional Spray, Dipping etc

### Application Instruction

Recommended method of application is conventional spray for large areas. However smaller areas can be brushed. The surface temperature before application should be 2°C - 3°C above dew point. Surface temperature above 50°C & relative Humidity above 85% should be avoided. Please check the compatibility of product with paint by mixing small volume and apply on surface to check the result until dried.

### Safety Precautions

Take normal precautions while applications such as, wearing safety gloves, face masks, and eye goggles. Sufficient ventilation should be provided while application. Observe all statutory local by-laws with respect to **health and safety** together with the laws governing storage of flammable liquid products. Keep the material away from sparks and open flame. Slight Skin irritation is observed when touched to bear skin. Avoid prolonged inhalation